

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 :

G01D 5/48, G01B 17/00

A1

(11) International Publication Number:

WO 93/15378

(43) International Publication Date:

5 August 1993 (05.08.93)

(21) International Application Number: PCT/US93/00957

(22) International Filing Date: 3 February 1993 (03.02.93)

(30) Priority data:
07/829,443


3 February 1992 (03.02.92) US

(71) Applicant: MTS SYSTEMS CORPORATION [US/US];
14000 Technology Drive, Eden Prairie, MN 55344 (US).(72) Inventors: GLODEN, Michael, L. ; 1012 Oakgate Court,
Apex, NC 27502 (US). PETERSON, Wade, Douglas ;
2422 H Gazebo Drive, Morrisville, NC 27560 (US).
RUSSELL, Lawrence, J. ; 902 Serviceberry Court,
Knightdale, NC 27545 (US).(74) Agent: BRUESS, Steven, C.; Merchant, Gould, Smith,
Edell, Welter & Schmidt, 3100 Norwest Center, 90 South
Seventh Street, Minneapolis, MN 55402 (US).(81) Designated States: CA, JP, KR, European patent (AT, BE,
CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL,
PT, SE).

Published

With international search report.

(54) Title: MODULAR MAGNETOSTRICTIVE DISPLACEMENT SENSOR



(57) Abstract

A modular magnetostrictive displacement sensor is disclosed having a waveguide of magnetostrictive material extending from a first housing and protected by a member of fiber reinforced composite material. There is circuitry in the first housing for generating electrical pulses along the waveguide and a converter for generating an electrical signal in response to a torsion pulse in the waveguide caused by a magnet disposed proximate the waveguide when the electrical pulse passes the magnet position. In one embodiment the waveguide and its protective member is received within a second housing. One or more magnets may be mounted within the second housing or externally on or near the second housing for movement to the waveguide. Alternatively the sensor may be used without the second housing.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LJ	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

MODULAR MAGNETOSTRICTIVE DISPLACEMENT SENSOR**BACKGROUND OF THE INVENTION**

The present invention relates to a position
5 sensor and, in particular, to a position sensor which
operates according to the principles described in U.S.
Patent No. 3,898,555 to Tellerman. In general, such
devices incorporate a sonic waveguide cooperating with a
magnet. The waveguide and magnet are mounted for
10 movement with respect to each other. The device
operates according to the principles of the Wiedemann
effect. An electrical pulse is generated resulting in a
magnetic field concentrated in the waveguide. The
magnetic field of the cooperating magnet causes a sonic
15 torsional pulse to be generated and travel along the
waveguide. This sonic torsional pulse is converted to
an electrical signal. The time interval between the
current pulse and the reception of the sonic torsional
pulse is representative of the location or position of
20 the magnet along the waveguide. Such devices therefore
provide an accurate indication of linear displacement,
for example, in machine tool applications where the
location of a machine element must be determined for the
control of machine functions.

25 The prior art also includes variable
potentiometer devices which have been a primary absolute
displacement measuring sensor because of the simplicity
of their operation, low cost, accuracy, and the ease
with which they interface with electronics. On the
30 other hand, this type of prior art sensor has several
disadvantages. The potentiometer has a sliding contact
and resistance element, both of which tend to wear with
extensive use. The wiper contact is sensitive to
contamination that in many machine applications is
35 difficult to control or eliminate. The cost of such
devices is also increased if it is necessary to convert
the analog signal output of the potentiometer for use
with digital controls.

Balluff of Germany has introduced a non-contact magnetostrictive displacement sensor which eliminates the disadvantages of potentiometer-type devices.

However, the Balluff device appears to have relatively
5 limited application wherein the magnet is mounted externally on the device housing for movement relative thereto. Also, the Balluff device does not achieve the cost benefits associated with potentiometer-type devices.

10 The present invention is directed toward providing a low cost magnetostrictive displacement sensor of modular design whereby it is adaptable to a wide range of machine requirements and applications and which incorporates other advantages of variable
15 potentiometer devices without their disadvantages.

SUMMARY OF THE INVENTION

The present invention is a modular magnetostrictive displacement sensor capable of use in a
20 wide variety of applications. It includes a first housing in which a waveguide formed of magnetostrictive material is mounted with the waveguide extending from the housing. A means for protecting the waveguide surrounds the waveguide and in the preferred embodiment
25 is a fiber reinforced composite material. There is provided a means for generating electrical pulses in a direction along the waveguide and a converter means is mounted in the first housing to generate an electrical signal in response to a torsion pulse in the waveguide
30 caused by at least one magnet adjacent the waveguide when an electrical current passes along the waveguide. There is a means responsive to the electrical signal for indicating the position of the magnet along the waveguide. In a preferred embodiment, the waveguide is
35 received within a second housing attached to said first housing. The second housing has a means for mounting a magnet therein for movement in a direction along the

longitudinal axis of the waveguide. The second housing is also provided with a means for mounting a magnet thereto externally on the housing also for movement in a direction along the longitudinal axis of the waveguide.

- 5 In either embodiment means are provided to restrain the magnet from moving laterally with respect to the waveguide longitudinal axis.

The displacement sensor of the present invention can be used in one application without the
10 second housing. In such applications, at least one magnet is positioned with respect to the waveguide for movement relative to the waveguide along its longitudinal axis. For example, the displacement sensor may be mounted in a fixed position with the magnet
15 mounted in close proximity to the waveguide on a movable machine member.

In other applications, the alternative embodiments of mounting the movable magnet within the second housing or on guide means externally on the
20 second housing may be desirable. The fiber reinforced composite protective member for the waveguide in the device of the present invention is particularly advantageous in that its thermal coefficient of expansion is very close to that of the waveguide
25 material itself. Because the waveguide in some embodiments is under tension, matching the thermal coefficient of expansion properties of the protective member with the waveguide stabilizes the sensor output signal and lowers measurement hysteresis.

30 These and other advantages of the present invention will become apparent with reference to the accompanying drawings, detailed description of the preferred embodiment and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a view in perspective illustrating the modular construction of the magnetostrictive displacement sensor of the present invention;

5 Figure 2 is a view in elevation of one embodiment of the present invention;

Figure 3 is an end view of the embodiment of Figure 2;

10 Figure 4 is a cross-sectional view taken generally along the lines 4-4 of Figure 3;

Figure 5 is a cross-sectional view taken generally along the lines 5-5 of Figure 2;

Figure 6 is a cross-sectional view taken generally along the lines 6-6 of Figure 2;

15 Figure 7 is a view in partial cross-section taken generally along the lines 7-7 of Figure 2;

Figure 8 is an enlarged fragmentary sectional view illustrating an alternative embodiment of the present invention wherein the waveguide is mounted under
20 tension.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to the drawings wherein like numerals represent like parts throughout the several views, the
25 modular magnetostrictive displacement sensor of the present invention is illustrated generally at 10. Sensor 10 includes a first member 12 and a second member 14. First member 12 can be used in some applications independently of second member 14. First member 12
30 includes a first housing 16. Extending from housing 16 is a tubular waveguide protective member 18. As will be described in more detail later, protective member 18 is in the preferred embodiment formed of a fiber reinforced composite material.

35 As shown in more detail in Figures 3-7, a magnetostrictive waveguide 20 has one end fixed to a mounting member 22 having a flange portion 24 anchored

in a bracket 26 within housing 16. Mounting member 22 is secured within bracket 26 by an anchor cap 27 which snap fits between lugs 26 on end portion 86 of first frame member 78.

5 Waveguide 20 is of the type well known in the prior art as shown, for example, in the Tellerman '555 patent referenced above. It is a tubular member formed of magnetostrictive material such as NI-SPAN-C alloy. An electrical conductive wire (not shown) extends
10 through the tubular member of waveguide 20 for transmitting electrical pulses along the direction of the waveguide. An electrical return wire 34 completes the pulse circuit. Electrical circuitry for generating the electrical pulses that are transmitted along
15 waveguide 20 is well known in the prior art and in the present invention such circuitry may be incorporated and/or mounted on printed circuit board 32. A second printed circuit board 36 may also be mounted within housing 16 and carry additional electrical circuit
20 components for the generation of the pulse signals and/or the processing of the return signal representative of the position of a magnet along waveguide 20. Again, such circuitry is also well known to those of ordinary skill in the art. A plurality of
25 pins 37 interconnect the circuit elements on printed circuit boards 32 and 36. In an alternative embodiment a flexible ribbon conductor may be used in place of rigid pins 37.

A converter means 40 is mounted on printed
30 circuit board 32 within housing 16. As is known in the prior art, converter means 40 functions to generate an electrical signal in response to a torsion pulse in the waveguide 20 which is caused by a magnet positioned along the waveguide when an electrical pulse passes
35 along the waveguide (the Wiedemann effect). In the preferred embodiment of the present invention, converter means 40 is like that disclosed in U.S. Patent No.

4,803,427 in that it includes a single transducer tape 42 attached to waveguide 20 at one end of tape 42. Tape 42 extends within an electrical coil 44 mounted in printed circuit board 32 and the end of tape 42 within coil 44 may or may not be anchored to coil 44. A permanent magnet 46 provides a magnetic biasing field for tape 42 and coil 44 according to the principles of what is known as the Villari effect. Movement of transducer tape 42 within coil 44 in response to a torsion pulse in waveguide 20 causes a change in the magnetic induction in coil 44 inducing a voltage in coil 44. The time interval between the electrical pulse that is transmitted along waveguide 20 and the electrical signal generated in coil 44 is a measure of the distance of a magnet positioned along waveguide 20 from a referenced position. It is well known to one of ordinary skill in the art to process the signal either digitally or by analog techniques to give an indication of position of the magnet along waveguide 20. One or more electrical conductors 48 may be provided to transmit power to the sensor from an external power source and transmit the processed signal information from sensor 10 through a conductor cable 50 extending from housing 16.

In one embodiment of the present invention, waveguide 20 is secured within protective member 18 without placing waveguide 20 under tension. In this embodiment as specifically shown in Figure 4, an end 52 of waveguide 20 is mounted to a damping member 54. Damping member 54 is provided to minimize reflections of sonic pulses from the terminal end of waveguide 20. Damping member 54 may be a rubber pad clamped about waveguide 20 which fits loosely within protective member 18. The construction of such damping elements is also well known in the art. A waveguide tail anchor 58 is affixed directly to waveguide 20. Protective member 18 is closed by a tube plug 60.

In an alternative embodiment, waveguide 20 may be mounted within protective member 18 under tension. In this embodiment as specifically shown in Figure 8, a modified tail anchor 62 is secured to waveguide 20. A damping member 66 is also provided in this embodiment. A spring cup 65 is enched by tube plug 60 to protective member 18 and extends about waveguide 20 and damping member 66. A spring retainer 63 is affixed to tail anchor 62 within a slot formed therein. Waveguide 20 is placed under tension by a spring 68 which engaged spring retainer 63 at one end and spring cup 65 at an end 69 thereof. A means may be provided to adjust the tension on spring 68 and thereby the tension on waveguide 20. The main reason for providing tension on waveguide 20 is to center waveguide 20 within protective member 18 thereby improving the accuracy of the device. Spring 68 is an extension spring. As shown in Figure 4, a plurality of spacers 70 may be positioned about waveguide 20 along protective member 18 to support waveguide 20. Generally there is a somewhat loose fit between spacers 70 and protective member 18. This loose fit allows easy waveguide piping during manufacturing operations and wider tolerances in spacers 70 and internal dimensions of protective member 18. Accordingly, during normal operation of the sensor, waveguide 20 moves within housing 18 in response to orientation, shock and vibration. This subjects waveguide 20 to slightly varying magnetic field intensities from a magnet in proximity thereto causing potential errors in sensor measurement. Tensioning waveguide 20 effectively controls and minimizes these effects through providing the centering benefit.

First housing 16 is in two parts comprising a first member 72 and a second member 74. Second member 74 has a base 76, a first frame member 78, and a second frame member 80. Frame member 78 has side portions 82 and 84 and an end portion 86. Waveguide mounting member

26 is integrally formed in end portion 86 of frame member 78. Printed circuit board 32 snap fits to frame member 78 and has a pair of tab portions 88 and 90 which are received within mating slots formed in base 76 as shown more specifically in Figure 7. First frame member 78 also has a bracket portion 92 in which is received waveguide protective member 18. Printed circuit board 36 also snap fits to second frame member 80 which has a pair of projecting tabs 94 and 96 which frictionally fit within holes (not shown) in printed circuit board 36. First member 72 of housing 16 has an internal partition wall 98 functioning to define housing chambers 100 and 102 in which printed circuit boards 32 and 36 are received, respectively. First and second members 72 and 74 are secured together by conventional fastening means such as screws so that they can be readily separated. The construction of first housing 16 including the snap fit placement of printed circuit boards 32 and 36 provides for ease of assembly as well as repair and replacement of component parts.

In one embodiment of the present invention, first member 12 is coupled to second member 14 as illustrated more specifically in Figures 2-5. Second member 14 comprises an extruded housing 104 and an end cap 106. Housings 104 and 16 are preferably formed of a non-magnetic material. Housing 104 can be provided in the length necessary for a particular application. Housing 104 defines an elongated chamber 108 in which may be mounted a magnet 110. Magnet 110 is secured on a rod 112 between a retainer ring 114 and a bearing member 116. Magnet 110 has a concave surface at 118 as shown in Figure 5 with a radius of curvature corresponding generally to the radius of curvature of tubular protective member 18. Bearing member 116 is attached to rod 112 by means of a conventional washer and screw 120 and 122, respectively. As shown more specifically in Figure 5, bearing member 116 has pairs of guide rails

124 and 126 oppositely disposed in sliding engagement with an inner surface 125 and 127 of extruded housing 104, respectively. Extruded housing 104 has a pair of oppositely disposed guide tracks 128 and 130 extending longitudinally within chamber 108. Bearing member 116 has another pair of guide rails 132 and 134 which slidably engage guide tracks 128 and 130, respectively. In this construction, magnet 110 may move freely along the longitudinal axis of waveguide 20, but is restrained from movement in a direction generally laterally with respect to waveguide 20. At its end opposite magnet 110, rod 112 is received within a bearing 136 which is held in end cap 106. An O-ring 140 seals rod 112 and is disposed between a recessed surface of end cap 106 and a wiper member 142. In the embodiment illustrated in Figures 2-5, sensor 10 may be mounted in a stationary position with end 144 of rod 112 attached by known means such as ball joints, studs, or clevis ends to a moving member. As magnet 110 moves within chamber 108 along waveguide 20, the torsion wave generated in waveguide 20 represents the position detected by the device.

An external guide track 146 may be provided as an alternative mounting means for a magnet corresponding to magnet 110. As shown in more detail in Figures 1 and 2, guide track 146 extends longitudinally along the length of housing 104 with a pair of flange portions 148 and 150 spaced above a surface 152 to define channels 154 and 156 in which mating legs (not shown) of a magnet may be captured. In this embodiment sensor 10 and the associated externally guided magnet are again mounted for movement with respect to each other with the magnet allowed to move freely along the longitudinal axis of waveguide 20 but restrained from movement laterally with respect to waveguide 20. In a similar alternative embodiment, a magnet may be mounted separately from sensor 10 yet in close proximity to waveguide 20.

In operation the present invention is useful in a wide variety of applications requiring linear displacement sensors. First member 12 can be used alone or in combination with second member 14. When used in
5 combination, the magnet movable with respect to the waveguide may be mounted within housing 104 or externally either on the housing or separate therefrom. While the present invention has been disclosed as incorporating one magnet, multiple magnets may be used
10 as well each mounted for movement with respect to waveguide 20 as described herein.

Waveguide protective member 18 as previously described is formed of a fiber reinforced composite material. In one embodiment it may be fiberglass
15 reinforced plastic which is a plastic resin matrix reinforced by embedded glass fibers. A high temperature vinyl-ester resin with ultraviolet stabilizers is suitable with a 60% to 70% glass fiber filler providing a low temperature coefficient of expansion, high
20 strength and high rigidity. Other filler materials such as quartz and carbon fibers may also be used. Protective member 20 may be formed by a pultrusion process which is well known in the art. An alternative manufacture method is a filament winding technique also
25 known in the art. The filament winding method provides benefits similar to that achieved by the pultrusion process.

In embodiments where the waveguide 20 is placed under tension within protective housing 18, the use of
30 the fiber reinforced composite material functions to more effectively control waveguide tension. This is because the temperature coefficient of expansion of the fiber reinforced composite material can be closely matched to that of the waveguide material which in a
35 preferred embodiment is as previously described NI-SPAN-C alloy. With closely matched temperature coefficients of expansion, the extension of spring 68 is maintained

nearly constant thereby minimizing the adverse effects of temperature on the sensor accuracy.

From the above description, it can be appreciated that the present invention provides a modular magnetostrictive displacement sensor capable of use in many varied applications. In addition to being easily adapted to a wide range of machine requirements, it has the cost benefits of the prior art variable potentiometer-type sensors while at the same time illuminating the disadvantages of such sensors such as sliding contact and resistance element wear and susceptibility to contamination. Moreover the present invention incorporating a fiber reinforced composite protective member for the magnetostrictive waveguide facilitates maintaining consistent and constant waveguide tensioning eliminating the adverse effects on sensor accuracy caused by thermal expansion. While specific embodiments are disclosed herein, it is understood that equivalent structures are also contemplated within the spirit and scope of the present invention.

WHAT IS CLAIMED IS:

1. A magnetostrictive displacement sensor comprising:

- 5 a first housing;
- a waveguide formed of magnetostrictive material;
- means for mounting one end of said waveguide in said first housing with said waveguide extending from said first housing;
- 10 means surrounding said waveguide for protecting said waveguide;
- a second housing attached to said first housing and having a first chamber therein in which said waveguide protective means is received;
- 15 means for generating electrical pulses in a direction along said waveguide;
- at least one magnet disposed proximate said waveguide;
- said second housing having a second
- 20 chamber and means within said second chamber for mounting said at least one magnet for movement in a direction along a longitudinal axis of said waveguide while restraining said magnet from movement in a direction generally laterally with respect to said
- 25 longitudinal axis;
- a converter means mounted in said first housing for generating an electrical signal in response to a torsion pulse in said waveguide caused by said at least one magnet when an electrical pulse reaches said
- 30 at least one magnet, at least one of said waveguide and said at least one magnet moveable with respect to the other;
- means responsive to said electrical signal for indicating the position of said at least one magnet
- 35 along said waveguide.

2. A magnetostrictive displacement sensor in accordance with claim 1 further comprising a rod attached to said magnet and extending from said second housing.

5

3. A magnetostrictive displacement sensor comprising:

a first housing;

a waveguide formed of magnetostrictive

10 material;

means for mounting one end of said waveguide in said first housing with said waveguide extending from said first housing;

15 protecting said waveguide;

a second housing attached to said first housing and having a first chamber therein in which said waveguide protective means is received;

20 means for generating electrical pulses in a direction along said waveguide;

at least one magnet disposed proximate said waveguide;

25 said second housing having guide means thereon for mounting said at least one magnet externally of said first chamber for movement in a direction along a longitudinal axis of said waveguide while restraining said magnet from movement in a direction generally laterally with respect to said longitudinal axis;

30 a converter means mounted in said first housing for generating an electrical signal in response to a torsion pulse in said waveguide caused by said at least one magnet when an electrical pulse reaches said at least one magnet, at least one of said waveguide and said at least one magnet moveable with respect to the
35 other;

means responsive to said electrical signal for indicating the position of said at least one magnet along said waveguide.

4. A magnetostrictive displacement sensor in
5 accordance with claim 1 or 3 wherein said converter means further comprises:

a transducer tape having one end fixed to said waveguide and an opposite end;

- an electrical coil receiving said opposite
10 end of said transducer tape, said electrical coil mounted on a printed circuit board within said first housing.

5. A magnetostrictive displacement sensor in
15 accordance with claim 4 wherein said first housing has a frame to which said printed circuit board is removably attached.

6. A magnetostrictive displacement sensor in
20 accordance with claim 5 further comprising a magnetic means mounted on said printed circuit board in proximity with said electrical coil and said tape for magnetically biasing said coil and said tape.

- 25 7. A magnetostrictive displacement sensor comprising:

a first housing;

a waveguide formed of magnetostrictive material and having first and second ends;

- 30 means for mounting said first end of said waveguide in said first housing with said waveguide extending from said first housing;

- a protective member surrounding said waveguide, said protective member formed of fiber
35 reinforced composite material;

at least one magnet disposed proximate said waveguide;

means for generating electrical pulses in a direction along said waveguide;

5 a converter means mounted in said first housing for generating an electrical signal in response to a torsion pulse in said waveguide caused by said at least one magnet when an electrical current pulse passes along said waveguide, at least one of said waveguide and said at least one magnet moveable with respect to the other;

10 means responsive to said electrical signal for indicating the position of said at least one magnet along said wave guide.

8. A magnetostrictive displacement sensor in accordance with claim 7 further comprising means for mounting said second end of said waveguide and applying tension to said waveguide along its longitudinal axis.

9. A magnetostrictive displacement sensor in accordance with claim 8 wherein said mounting and tensioning means further comprises a spring having one end thereof fixed to said protective member and an opposite end thereof fixed to said waveguide.

25 10. A magnetostrictive displacement sensor comprising:

a first housing;

a waveguide formed of magnetostrictive material, said waveguide having first and second ends;

30 means for mounting said first end of said waveguide in said first housing with said waveguide extending from said first housing;

a protective member surrounding said waveguide and formed of material having a thermal coefficient of expansion substantially the same as the thermal coefficient of expansion of said waveguide magnetostrictive material;

at least one magnet disposed proximate
said waveguide;

means for generating electrical pulses in
a direction along said waveguide;

5 a printed circuit board removably mounted
within said first housing;

a converter means mounted on said printed
circuit board for generating an electrical signal in
response to a torsion pulse in said waveguide caused by
10 said at least one magnet and created by the Wiedemann
effect, at least one of said waveguide and said at least
one magnet moveable with respect to the other;

means responsive to said electrical signal
for indicating the position of the magnet along said
15 waveguide.

11. A magnetostrictive displacement sensor in
accordance with claim 10 wherein said protective member
is formed of fiber reinforced composite material.

20 12. A magnetostrictive displacement sensor in
accordance with claim 10 wherein said converter means
comprises a transducer tape affixed at one end to said
waveguide and an electrical coil, said tape received
25 within said coil.

1/5

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



5/5

FIG. 7





FIG. 8



INTERNATIONAL SEARCH REPORT

PCT/US 93/00957

International Application No.

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all)⁶

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 G01D5/48; G01B17/00

II. FIELDS SEARCHEDMinimum Documentation Searched⁷

Classification System

Classification Symbols

Int.Cl. 5

G01D ; G01B

Documentation Searched other than Minimum Documentation
to the extent that such Documents are Included in the Fields Searched⁸**III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹**

Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
Y A	US,A,4 952 873 (JACOB TELLERMAN) 28 August 1990 see the whole document	7 1,3,4, 8-10
A	FR,A,2 523 719 (MERLIN GERIN) 23 September 1983 see figure 1	1-3
A	US,A,4 803 427 (MASON ET AL.) 7 February 1989 see column 1, line 44 - column 4, line 33	5
Y A	WO,A,9 114 151 (HITACHI CONSTRUCTION MACHINERY CO. LTD.) 19 September 1991 see abstract	7 11

¹⁰ Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

20 APRIL 1993

Date of Mailing of this International Search Report

29.04.93

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

LUT K.

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.**

US 9300957
SA 70392

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20/04/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4952873	28-08-90	EP-A- 0442985 JP-T- 4501919 WO-A- 9104457	28-08-91 02-04-92 04-04-91
FR-A-2523719	23-09-83	DE-A- 3309089 US-A- 4604576	29-09-83 05-08-86
US-A-4803427	07-02-89	None	
WO-A-9114151	19-09-91	EP-A- 0471073	19-02-92